

7.4.3.2 Table of segregation of freight containers on board container ships with closed cargo holds (Amdt. 40-20)

SEGREGATION REQUIREMENT	VERTICAL			HORIZONTAL						
	CLOSED VERSUS CLOSED	CLOSED VERSUS OPEN	OPEN VERSUS OPEN		CLOSED VERSUS CLOSED		CLOSED VERSUS OPEN		OPEN VERSUS OPEN	
					ON DECK	UNDER DECK	ON DECK	UNDER DECK	ON DECK	UNDER DECK
"AWAY FROM" .1	ONE ON TOP OF THE OTHER PERMITTED	OPEN ON TOP OF CLOSED PERMITTED OTHERWISE AS FOR "OPEN VERSUS OPEN"	NOT IN THE SAME VERTICAL LINE UNLESS SEGREGATED BY A DECK	FORE AND AFT	NO RESTRICTION	NO RESTRICTION	NO RESTRICTION	NO RESTRICTION	ONE CONTAINER SPACE	ONE CONTAINER SPACE OR ONE BULKHEAD
				ATHWART-SHIPS	NO RESTRICTION	NO RESTRICTION	NO RESTRICTION	NO RESTRICTION	ONE CONTAINER SPACE	ONE CONTAINER SPACE
FORE AND AFT	ONE CONTAINER SPACE	ONE CONTAINER SPACE OR ONE BULKHEAD		ONE CONTAINER SPACE	ONE CONTAINER SPACE OR ONE BULKHEAD	ONE CONTAINER SPACE	ONE BULKHEAD			
ATHWART-SHIPS	ONE CONTAINER SPACE	ONE CONTAINER SPACE		ONE CONTAINER SPACE	TWO CONTAINER SPACES	TWO CONTAINER SPACES	ONE BULKHEAD			
FORE AND AFT	ONE CONTAINER SPACE	ONE BULKHEAD		ONE CONTAINER SPACE	ONE BULKHEAD	TWO CONTAINER SPACES	TWO BULKHEADS			
ATHWART-SHIPS	TWO CONTAINER SPACES	ONE BULKHEAD		TWO CONTAINER SPACES	ONE BULKHEAD	THREE CONTAINER SPACES	TWO BULKHEADS			
"SEPARATED FROM" .2	NOT IN THE SAME VERTICAL LINE UNLESS SEGREGATED BY A DECK	AS FOR "OPEN VERSUS OPEN"		FORE AND AFT	MINIMUM HORIZONTAL DISTANCE OF 24 M	ONE BULKHEAD AND MINIMUM HORIZONTAL DISTANCE OF 24 M*	MINIMUM HORIZONTAL DISTANCE OF 24 M	TWO BULKHEADS	MINIMUM HORIZONTAL DISTANCE OF 24 M	TWO BULKHEADS
				ATHWART-SHIPS	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED
"SEPARATED BY A COMPLETE COMPARTMENT OR HOLD FROM" .3	NOT IN THE SAME VERTICAL LINE UNLESS SEGREGATED BY A DECK	AS FOR "OPEN VERSUS OPEN"		FORE AND AFT	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED
				ATHWART-SHIPS	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED
"SEPARATED LONGITUDINALLY BY AN INTERVENING COMPLETE COMPARTMENT OR HOLD FROM" .4	PROHIBITED			FORE AND AFT	MINIMUM HORIZONTAL DISTANCE OF 24 M	ONE BULKHEAD AND MINIMUM HORIZONTAL DISTANCE OF 24 M*	MINIMUM HORIZONTAL DISTANCE OF 24 M	TWO BULKHEADS	MINIMUM HORIZONTAL DISTANCE OF 24 M	TWO BULKHEADS
	PROHIBITED			ATHWART-SHIPS	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED	PROHIBITED

* containers not less than 6 m from intervening bulkhead.

Note: all bulkheads and decks shall be resistant to fire and liquid.